

Calipers

An industry standard in measuring tools

Offset Caliper

SERIES 573, 536 — ABSOLUTE Digimatic and vernier type

- The beam-mounted jaw can be adjusted to facilitate measurement of stepped sections and hard-to-get-at workpiece features.
- Digital models are IP67 Absolute type. No need to reset the origin after switching on. (Refer to page D-8 for a description of Absolute measurement.)
- Allows integration into statistical process control and measurement systems for models with measurement data output connector. Refer to page A-3.



573-601
ABSOLUTE™

536-101

SPECIFICATIONS

Metric	Digital model	
Order No.	Range	Accuracy
573-601	0 - 150mm	±0.02mm
573-611*	0 - 150mm	±0.02mm
573-602	0 - 200mm	±0.02mm
573-612*	0 - 200mm	±0.02mm
573-604	0 - 300mm	±0.03mm
573-614*	0 - 300mm	±0.03mm

* Without thumb roller

Metric	Analog model	
Order No.	Range	Accuracy
536-101	0 - 150mm	±0.05mm
536-102	0 - 200mm	±0.05mm
536-103	0 - 300mm	±0.08mm

Inch/Metric	Digital model	
Order No.	Range	Accuracy
573-701	0 - 6"	±.001"
573-702	0 - 8"	±.001"
573-704	0 - 12"	±.0015"

DIMENSIONS

Analog model

Digital model

Unit: mm



Order No.	Model	Range	D	G	J	N	W
573-601	Digital model	0 - 150mm	40	10	30	10	95
573-602		0 - 200mm	50	10	38.5	10	95
573-604		0 - 300mm	64	15	51	15	135
536-101	Analog model	0 - 150mm	40	10	30	10	95
536-102		0 - 200mm	50	10	38.5	10	95
536-103		0 - 300mm	64	15	51	15	135



(Refer to page X for details.)



(Refer to page X for details.)



Technical Data

Accuracy: Refer to the list of specifications. (excluding quantizing error for digital models)
 Resolution*: 0.01mm or .0005"/0.01mm
 Graduation**: 0.05mm
 Display*: LCD
 Scale type*: ABSOLUTE electromagnetic induction linear encoder
 Max. response speed*: Unlimited
 Battery: **SR44** (1 pc), **938882**, for initial operational checks (standard accessory)
 Battery life*: Approx. 3 years under normal use (1 year: 300mm model)
 Dust/Water protection level*: IP67 (IEC 60529)***
 * Digital models ** Analog models
 *** This model is not waterproof type.
 Therefore, rustproofing shall be applied after use.

Optional accessories for Digital Model

For details, refer to page D-39.
959143: Data hold unit
 Connecting cables for IT/DP/MUX
05CZA624: SPC cable with data button (1m)
05CZA625: SPC cable with data button (2m)
USB Input Tool Direct
06ADV380A: SPC cable for **USB-ITN-A** (2m)
 Connecting cables for **U-WAVE-T**
02AZD790A: SPC cable for **U-WAVE** with data button (160mm)
02AZE140A: SPC cable for footswitch